



BONDCRETE BONDING AGENT WB

TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

BONDCRETE BONDING AGENT (WATER BASED) is bonding primer for smooth and sealed substrates. It contains a special polymeric curing agent that provides the film with a high degree of adhesion and stability.



RECOMMENDED APPLICATIONS

- ✓ for bonding new cementitious materials to existing cementitious concrete
- ✓ for use on horizontal and vertical surfaces where the concrete or mortar can be supported by formwork
- ✓ ideal for extension and repair to concrete in Factories, Loading bays, Trucking aisles Bridges and Roads, Cementitious floor toppings



ADVANTAGES

- ✓ Can be applied on damp surface, dry surface
- ✓ Designed for industrial application
- ✓ Excellent adhesion between new and old concrete/mortar
- ✓ Sealing concrete pavement and structure against intrusion of water
- ✓ Prevents corrosion of rebars



PRODUCT INFORMATION

COLOR	:	Milky White
PACKAGING	:	1 gallon and 20L pail
STORAGE	:	Store in a cool, dry place, away from direct sunlight.
SHELF LIFE	:	12 months from manufacturing date



ENVIRONMENT

Our facility complies with the proper waste management procedures. Our products are also free of ozone depleting substances.



APPLICATION INSTRUCTION

SURFACE PREPARATION

All concrete or mortar surface to be treated must be firm, dust free, oil free and clean. All laitance should be removed mechanically. The surface should be thoroughly washed off with clean water and any surface ponded water should be removed.

APPLICATION.

Mix **BONDCRETE BONDING AGENT WB** before applying the product. It should be applied to the prepared surface by paintbrush, roller or spray. Pour fresh concrete while **BONDCRETE BONDING AGENT WB** is still wet or tacky.

The curing interval per coat may vary depending on the topping and type of application (patching, overlayment, horizontal or vertical).



COVERAGE

20-30 sqm per gallon at 1 coat
120-150 sqm per 20L pail at 1 coat



SUSTAINABILITY

Our company is committed to Carbon Neutrality through our various programs such as our GHG Emission Reduction Logistics Approach and OPTI Trees Planting Program.



HEALTH & SAFETY

BONDCRETE BONDING AGENT WB is non-toxic and non-flammable.



QUALITY & DURABILITY ASSURANCE

Our stringent Quality Assurance Procedure for every batch of products manufactured. Our R&D Laboratory based in our production facility ensures that scientific Quality Control Parameters are measured for quality.

Our Quality Control Parameters ensure the stability of our products, ensuring the long-term durability amid exposure to various element and weather conditions.

COLORZONE VENTURES CORPORATION

ADDRESS: BLK 1 LOT 6 KIANA BLDG, SOLUNA COMMERCIAL BACOR BLVD. CITY OF BACOR CAVITE

EMAIL: colorzoneph@gmail.com

CONTACT NO: +6346 238 2133 / +63 917 817 3960