



NATURAL SAND FINISH

TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

NATURAL SAND FINISH is a premium grade wall finishing system with maximum stability and bonding strength, perfect for interior and exterior industrial finish.



RECOMMENDED APPLICATIONS

- Specially designed for special natural stone design applications
- Can be applied to drywall, concrete, masonry substrates and EIFS
- Used as a reflective and decorative type waterproofing



ADVANTAGES

- Ready mix product available in a wide range of colors
- It provides the owner, architects, designers with a new level of durability and performance in an elegant architecture finish.
- Can be applied to drywall, concrete, masonry substrates and EIFS



PRODUCT INFORMATION

COLOR: Color variants available

GRADE: rough and fine

DRYING TIME : Touch dry approximately 4 hours depending on thickness and temperature.

PACKAGING : 30 kgs

STORAGE : Store in a cool, dry place, away from direct sunlight.

SHELF LIFE : 12 months from manufacturing date



ENVIRONMENT

Our facility complies with the proper waste management procedures. Our products are also free of ozone depleting substances.



SUSTAINABILITY

Our company is committed to Carbon Neutrality thru our various programs such as our GHG Emission Reduction Logistics Approach and OPTI Trees Planting Program.



APPLICATION INSTRUCTION

Mix **NATURAL SAND FINISH** for approximately 1 minute until uniform or homogeneous consistency is achieved using appropriate mixing paddle attached to a low-speed electric drill. Apply **NATURAL SAND FINISH** directly onto the surface using a clean trowel. Maintain a wet edge by applying and texturing continually over the surface until an entire wall section is completely covered.



COVERAGE

Approximately 10-12sqm per coating. Coverage figures are theoretical based on wastage factors, variety and nature of possible substrates.



HEALTH & SAFETY

NATURAL SAND FINISH is non-toxic and non-flammable.



QUALITY & DURABILITY ASSURANCE

Our stringent Quality Assurance Procedure for every batch of products manufactured. Our R&D Laboratory based in our production facility ensures that scientific Quality Control Parameters are measured for quality.

Our Quality Control Parameters ensure the stability of our products, ensuring the long-term durability amid exposure to various element and weather conditions.

COLORZONE VENTURES CORPORATION

ADDRESS: BLK 1 LOT 6 KIANA BLDG, SOLUNA COMMERCIAL BACOR BLVD.CITY OF BACOR CAVITE

EMAIL: colorzoneph@gmail.com

CONTACT NO: +6346 238 2133 / +63 917 817 3960