



PREMIUM PUTTY

TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

PREMIUM PUTTY is a premium all-purpose, acrylic based, moisture resistant putty used for a wide range of applications where a smooth base preparation is required. This can also be used for filling of pinholes, surface corrections, hairline cracks, non-structural filling and any surface repair for wood, concrete, fiber cement and fiber boards.



RECOMMENDED APPLICATIONS

- Filling of pinholes
- Filling of joints between gypsum boards, plywood and concrete fiber cement boards
- Surface patching
- Non-structural repairs



ADVANTAGES

- Excellent adhesion to wood, concrete, fiber cement and other fiber boards substrate
- Excellent non-sag properties that give good workability on both vertical and overhead applications
- Easy to apply and sand
- Minimal shrinkage
- Moisture resistant
- Long term durability
- High flexural strength
- Low VOC content for environmental compliance



PRODUCT INFORMATION

APPEARANCE: Smooth, creamy paste
COLOR: White
COMPATIBILITY: Compatible with latex, acrylic and oil based paints
DRYING TIME: 2-3 hrs touch dry
ODOR: Odorless
PACKAGING: 1.5kg/5kg/25kg pail
STORAGE: Store in a cool, dry place, away from direct sunlight
SHELF LIFE: 12 months



COVERAGE

Approximately 1.5-2.0 kg/m²



TECHNICAL INFORMATION

pH: 9.46
Hardnes Rating: 2B
Specific Gravity: 1.75 kg/l
Viscosity: 90.6 ku
VOC Content: <10 g/L



APPLICATION INSTRUCTION

SURFACE PREPARATION All surfaces must be smooth, sound and free from debris. Surfaces must be free from oil contamination. Concrete surfaces must be free from any trace of release oils and curing compound. Prior to application, wet substrate well with clean water especially for outdoor application & during extreme hot weather conditions. Apply the **PREMIUM PUTTY** using a steel trowel. Thin putty will dry in about 60 minutes depending on temperature and porosity of substrate.

Note: No further addition of water is required.



SUSTAINABILITY

Our company is committed to Carbon Neutrality thru our various programs such as our GHG Emission Reduction Logistics Approach and OPTI Trees Planting Program.



HEALTH & SAFETY

PREMIUM PUTTY is non-toxic, however safety gloves should be worn during application. Refer to Material Safety Data Sheet for more information on Health and Safety.



QUALITY & DURABILITY ASSURANCE

Our stringent Quality Assurance Procedure for every batch of products manufactured. Our R&D Laboratory based in our production facility ensures that scientific Quality Control Parameters are measured for quality.

Our Quality Control Parameters ensure the stability of our products, ensuring the long-term durability amid exposure to various element and weather conditions.

COLORZONE VENTURES CORPORATION

ADDRESS: BLK 1 LOT 6 KIANA BLDG, SOLUNA COMMERCIAL BACOR BLVD.CITY OF BACOR CAVITE

EMAIL: colorzoneph@gmail.com

CONTACT NO: +6346 238 2133 / +63 917 817 3960