



STUCCO PREMIUM WALL FINISH

TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

STUCCO PREMIUM WALL FINISH is textured white cement based exterior wall finish applicable for concrete substrate



RECOMMENDED APPLICATIONS

For interior use only for bare application.

Can be applied on exterior, but top coat is required.



ADVANTAGES

Provides quality textured finish on concrete walls.

Paintable. Use latex paints



PRODUCT INFORMATION

Color: White and Gray

Pot Life: 1 Hour

Packaging: 25kg bag

Storage: Store in a cool, dry place, away from direct sunlight.

Shelf Life: 12 months from manufacturing date.



ENVIRONMENT

Our facility complies with the proper waste management procedures. Our products are also free of ozone depleting substances.



SUSTAINABILITY

Our company is committed to Carbon Neutrality thru our various programs such as our GHG Emission Reduction Logistics Approach and OPTI Trees Planting Program.



APPLICATION INSTRUCTION

MIXING

Use a plastic pail/container. Place 5-6 liters of clean water, then slowly pour **STUCCO PREMIUM WALL FINISH**. While pouring, use an electric hand mixer to slowly mix the product. Mix it for approximately 3-5 minutes until you create a homogenous mixture. Depending on the ambient temperature and the desired consistency, the amount of water required may vary slightly but should not exceed 6.0 liters per 25kg bag of **STUCCO PREMIUM WALL FINISH**.

SURFACE PREPARATION

All surfaces must be smooth, sound and free from debris. Surfaces must be free from oil contamination. Concrete surfaces must be free from any trace of release oils and curing compound. Prior to application, wet substrate well with clean water especially for outdoor application & during extreme hot weather conditions. Apply the mixed **STUCCO PREMIUM WALL FINISH** on concrete walls using a steel trowel. 1-10 minutes after spreading the product using a steel trowel, use a finishing trowel to float the texture. A random circular motion is recommended until texture of the product looks exposed.

Note: finishing trowel can be either of the following: wood, pvc, foam trowels, others.

COVERAGE

10sqm/bag theoretical but will vary depending on substrate, thickness, and texture of application



HEALTH & SAFETY

STUCCO PREMIUM WALL FINISH is non-toxic but it is alkaline. A dust mask should be used when handling **STUCCO PREMIUM WALL FINISH**. Gloves should be worn during application. Refer to Material Safety Data Sheet for more information on Health and Safety.



QUALITY & DURABILITY ASSURANCE

Our stringent Quality Assurance Procedure for every batch of products manufactured. Our R&D Laboratory based in our production facility ensures that scientific Quality Control Parameters are measured for quality.

Our Quality Control Parameters ensure the stability of our products, ensuring the long-term durability amid exposure to various element and weather conditions.

COLORZONE VENTURES CORPORATION

ADDRESS: BLK 1 LOT 6 KIANA BLDG, SOLUNA COMMERCIAL BACOR BLVD.CITY OF BACOR CAVITE

EMAIL: colorzoneph@gmail.com

CONTACT NO: +6346 238 2133 / +63 917 817 3960