



SKIMCOAT SUPERFINO

TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

SKIMCOAT SUPERFINO is a finishing cementitious, thin plastering mortar formulated for interior and exterior application for concrete surface and pre-casts. SKIMCOAT SUPERFINO is a one product that is easy to apply and exhibits excellent properties for rendering work of 1-5mm thickness. It also reduces construction costs by replacing three applications – concrete neutralizer, patching compound and flat latex as primer.



RECOMMENDED APPLICATIONS

- Thin plastering
- Filling pinholes prior to over coating
- Interior and exterior application



ADVANTAGES

- Excellent bond to the concrete substrate
- Excellent non-sag properties that give good workability on both vertical and overhead applications
- No chalking, cracking or flaking
- Long term durability



PRODUCT INFORMATION

COLOR : White and Gray

POT LIFE : Approximately 1 hour depending on ambient conditions

PACKAGING : 20 kg bag

STORAGE : Store in a cool, dry place, away from direct sunlight.

SHELF LIFE : 12 months from manufacturing date



TECHNICAL INFORMATION

Compressive Strength at 28 days: 1,585 psi
Tensile Adhesion Strength at 3 days: 0.8 Mpa



ENVIRONMENT

Our facility complies with the proper waste management procedures. Our products are also free of ozone depleting substances.



SUSTAINABILITY

Our company is committed to Carbon Neutrality thru our various programs such as our GHG Emission Reduction Logistics Approach and OPTI Trees Planting



APPLICATION INSTRUCTION

PREPARATION

All surfaces must be smooth, sound and free from debris. Surfaces must be free from oil contamination. Concrete surfaces must be free from any trace of release oils and curing compound. Prior to application, wet substrate well with clean water especially for outdoor application & during extreme hot weather conditions. Apply the mixed **SKIMCOAT SUPERFINO** using a steel trowel. Thin skim coating will dry in about 30– 45 minutes depending on temperature and porosity of substrate. Smoothen the skim coat with soft paint brush or troweled

Note: No further addition of water to unused plaster is required.

SKIMCOAT SUPERFINO may be over coated with a decorative coating after 48 hours depending on the ambient condition.

MIXING

Using a plastic container, place 6.8 to 7 liters of clean water in the container and add 20 kg of **SKIMCOAT SUPERFINO**. Mix thoroughly using a slow speed electric drill fitted with an electric paddle for 3 – 5 minutes until desired homogeneous paste is achieved. Depending on the ambient temperature and the desired consistency, the amount of water required may vary slightly but should not exceed 7.0 liters per 20 kg bag of **SKIMCOAT SUPERFINO**. Always add powder to water.



COVERAGE

20sqm per 20kg bag at 1mm thickness



HEALTH & SAFETY

SKIMCOAT SUPERFINO is non-toxic but it is alkaline. A dust mask should be used when handling **SKIMCOAT SUPERFINO**. Gloves should be worn during application. Refer to Material Safety Data Sheet for more information on Health and Safety.



QUALITY & DURABILITY ASSURANCE

Our stringent Quality Assurance Procedure for every batch of products manufactured. Our R&D Laboratory based in our production facility ensures that scientific Quality Control Parameters are measured for quality.

Our Quality Control Parameters ensure the stability of our products, ensuring the long-term durability amid exposure to various element and weather conditions.

COLORZONE VENTURES CORPORATION

ADDRESS: BLK 1 LOT 6 KIANA BLDG, SOLUNA COMMERCIAL BACOR BLVD.CITY OF BACOR CAVITE

EMAIL: colorzoneph@gmail.com

CONTACT NO: +6346 238 2133 / +63 917 817 3960