



SUPERFINO PASTE TYPE SKIMCOAT

TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

SUPERFINO PASTE TYPE SKIMCOAT is a premier skimcoat formulated to be mixed with cement for interior and exterior application for concrete surface and pre-casts. **SUPERFINO PASTE TYPE SKIMCOAT** is easy to apply and exhibits excellent properties. It also reduces construction costs by replacing three applications – concrete neutralizer, patching compound and flat latex as primer. It is used to even surfaces up to 1–5mm thick to face up most types of masonry.



RECOMMENDED APPLICATIONS

- Thin plastering
- Filling pinholes prior to over coating
- Interior and Exterior



ADVANTAGES

- Excellent bond to the concrete substrate
- Excellent non-sag properties that give good workability on both vertical and overhead applications
- No chalking, cracking or flaking
- Long term durability
- Economical and easy to use



PRODUCT INFORMATION

COLOR : Off white liquid

WORKING TIME : Approximately 1 hour

PACKAGING : 25kg pail

STORAGE : Store in a cool, dry place, away from direct sunlight.

SHELF LIFE : 12 months from manufacturing date.



TECHNICAL INFORMATION

Compressive Strength at 28 days: 2,321 psi



ENVIRONMENT

Our facility complies with the proper waste management procedures. Our products are also free of ozone depleting substances.



SUSTAINABILITY

Our company is committed to Carbon Neutrality through our various programs such as our GHG Emission Reduction Logistics Approach and OPTI Trees Planting Program.



APPLICATION INSTRUCTION

SURFACE PREPARATION All surfaces must be smooth, sound and free from debris. Surfaces must be free from oil contamination. Concrete surfaces must be free from any trace of release oils and curing compound. Prior to application, wet substrate well with clean water especially for outdoor application & during extreme hot weather conditions. Apply the mixed **SUPERFINO PASTE TYPE SKIMCOAT** using a steel trowel. Thin skim coating will dry in about 30–45 minutes depending on ambient conditions and porosity of substrate. Smoothen the skim coat with soft paint brush or troweled

Note: Addition of water is not recommended on the unused resulting compound.

OPTIMUM SKIMCOAT may be over coated with a decorative coating after 48 hours depending on the ambient condition.

MIXING

Using a plastic container, mix **SUPERFINO PASTE TYPE SKIMCOAT** with 0.8-1 part of cement. Mix thoroughly using a slow speed electric drill fitted with paddle for 3 – 5 minutes until desired homogeneous paste is achieved.



COVERAGE

40-50sqm per pail (when mixed with equal parts of cement) at 1mm thickness. Coverage may vary depending on site condition.



HEALTH & SAFETY

SUPERFINO PASTE TYPE SKIMCOAT is non-toxic but it is alkaline. Gloves should be worn during application. Refer to Material Safety Data Sheet for more information on Health and Safety.



QUALITY & DURABILITY ASSURANCE

Our stringent Quality Assurance Procedure for every batch of products manufactured. Our R&D Laboratory based in our production facility ensures that scientific Quality Control Parameters are measured for quality. Specific Quality Control Parameters ensure the stability of our products, ensuring the long-term durability amid exposure to various element and weather conditions.

COLORZONE VENTURES CORPORATION

ADDRESS: BLK 1 LOT 6 KIANA BLDG, SOLUNA COMMERCIAL BACOR BLVD.CITY OF BACOR CAVITE

EMAIL: colorzoneph@gmail.com

CONTACT NO: +6346 238 2133 / +63 917 817 3960