



SUPERFINO SKIMCOAT READY TO USE



TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

SUPERFINO SKIMCOAT READY TO USE (RTU) is a paste type finishing cementitious, thin plastering mortar formulated to have a lasting hydrophobic property suitable for exterior and interior applications. It also reduces construction costs by replacing three applications – concrete neutralizer, patching compound and flat latex as primer. It is used to even surfaces up to 1 – 4mm thick to face up most types of masonry.



RECOMMENDED APPLICATIONS

- Thin plastering exterior walls
- Filling pinholes prior to over coating
- Interior and Exterior applications over concrete, fiber cement



ADVANTAGES

- Excellent bond to concrete, fiber cement boards, brick walls and AAC blocks
- Impressive water repellant property
- Significant project cost saver as this can already replace the use of flat latex
- Anti-mold and mildew
- High flexural strength therefore having an impressive crack bridging capability
- The paste consistency allows for easy application and excellent workability, ensuring a professional finish
- No chalking, cracking or flaking
- Long term durability



PRODUCT INFORMATION

COLOR: White

APPEARANCE: Smooth Paste

DENSITY: 1.8 g/ml

COVERAGE: 40 sqm at 0.5 mm thickness (1 coat)

COVERAGE: 40 sqm at 0.5 mm thickness (1 coat)

DRYING TIME: 4-5 mins for the first coat and 15-25 mins for the second coat depending on ambient conditions and the substrate's porosity

SHELF LIFE : 12 months from manufacturing date



TECHNICAL INFORMATION

Pull-off Strength at 3 days: 2.5 MPa

Tensile Adhesion Strength at 7days: 3.54 MPa

Flexural Strength at 7 days: 1.76 MPa

Shore A Hardness: B

Curing Time: 24hrs



APPLICATION INSTRUCTION

PREPARATION

All surfaces must be smooth, sound and free from debris. Surfaces must be free from oil contamination. Concrete surfaces must be free from any trace of release oils and curing compound. Prior to application, wet substrate well with clean water especially for outdoor application. Apply **SUPERFINO SKIMCOAT READY TO USE (RTU)** using a steel trowel. Allow the skim coat to dry for 4 to 10 mins for the first coat. Final curing of the 2nd coat is from 10-20 mins. This may vary depending on ambient conditions.

After 2-3 hrs, lightly sand the surface to achieve a smooth and even texture using a 100 to 120 grit sanding paper. Afterwhich, a 400 grit sanding paper may be used depending on the client's requirement.

SUPERFINO SKIMCOAT READY TO USE (RTU) / ALL WEATHER may be over coated with a decorative coating after 24 hours depending on the ambient condition.

As **SUPERFINO SKIMCOAT READY TO USE (RTU)** has an impressive hydrophobic property, priming the substrate with a Flat Latex paint is no longer required.



SUSTAINABILITY

Our company is committed to Carbon Neutrality thru our various programs such as our GHG Emission Reduction Logistics Approach and OPTI Trees Planting



COVERAGE

40 sqm per 20kg pail at 0.5mm thickness (1 coat)



HEALTH & SAFETY

SUPERFINO PREMIUM SKIMCOAT READY TO USE (RTU) is non-toxic but it is alkaline. A dust mask should be used when handling this product. Gloves should be worn during application. Refer to Material Safety Data Sheet for more information on Health and Safety.



QUALITY & DURABILITY ASSURANCE

Our stringent Quality Assurance Procedure for every batch of products manufactured. Our R&D Laboratory based in our production facility ensures that scientific Quality Control Parameters are measured for quality.

Our Quality Control Parameters ensure the stability of our products, ensuring the long-term durability amid exposure to various element and weather conditions.

COLORZONE VENTURES CORPORATION

ADDRESS: BLK 1 LOT 6 KIANA BLDG, SOLUNA COMMERCIAL BACOOR BLVD.CITY OF BACOOR CAVITE

EMAIL: colorzoneph@gmail.com

CONTACT NO: +6346 238 2133 / +63 917 817 3960